

Designated Building Product: Class 1

Version 1.0 December 2023

Declaration

Belgotex New Zealand has provided this declaration to satisfy the provisions of Building (Building Product Information Requirements) Regulations 2022. See [regulations](#).

Company Details

Name	Belgotex New Zealand Limited
Role	Supplier
NZBN	9429038353000
Address	25 Leslie Hills Drive, Riccarton, Christchurch 8011
Website	www.belgotex.co.nz
Email	product@belgotex.co.nz
Phone	0800-377-753

Product

Rubber underlay as specified on our [range statement](#).

Description of Broadloom Carpet

The term rubber underlay is taken to mean sheet rubber supplied in roll format to be used as an underlay under wall – to -wall floor covering products.

Belgotex (NZ) Ltd supplies rubber underlay comprising of recycled rubber. Rubber underlay can be either laid loosely, with double sided tape, or adhesive and is supplied by linear meter, or full rolls.

When installed a Belgotex (NZ) Ltd rubber underlay may contribute to G6 (airborne & impact sound) of the building. Compliance with this clause would need to be established as part of the proposed flooring system.

Building Code Obligations

When installed Belgotex Carpet Tiles meet the requirements under the building code as detailed below.

Code Clauses	Compliance Pathway	Evidence
B2 (Durability) B2.3.1(c)	Alternative Solution	Carpet tiles are manufactured in accordance with ISO9001:2015 and/or EN 14041 CE Mark, under EN 1307. B2/VM1 1.1.1 In-service history, Belgotex NZ supply rubber flooring in that has an expected lifespan of more than 15years with a product exceeding a service life of a minimum 5 years satisfying the performance requirements of the Building Code as a floor covering is easy to access and replace, and failure of the product would be easily detected during normal use of the product
C3 (Fire Affecting areas beyond the fire source)	Acceptable Solution	All products covered by this statement have been tested in accordance with ISO9239-1:2010 ¹ .

C3.4(b)		
D1 (Access Routes) D1.3.3 (d)	Acceptable Solution	Slip Testing to AS/NZS 4586-2004.
F2 (Hazardous building materials) F2.3.1	Verification Method	Product is tested for VOC Emissions.

Test reports available at www.belgotex.co.nz

¹Special order product testing will be provided at time of specification.

Scope of use and Limitations

Scope	Limitation
For all building classified uses.	<ul style="list-style-type: none">• Interior use only• Rubber underlay must be installed using the specified adhesive as per our range statement.• Substrate preparation must be undertaken according to the specified adhesive instructions.
For use as a flooring in an access route.	Rubber underlay are suitable for an access route.
In connection with underfloor heating including in-slab piped water heating.	Rubber underlay is suitable for use with underfloor heating up to 27 ^o c.

Conditions of use

Belgotex Rubber underlay must be installed according to manufacturers installation guidelines and maintained according to Belgotex New Zealand's care and maintenance guidelines available at www.belgotex.co.nz.

Additional Information

For all specification, installation, maintenance and warranty information and all information supporting Belgotex New Zealand's claims refer to www.belgotex.co.nz

No Belgotex Rubber Products are subject to a ban issued under [Section 26 of the Building Act](#).

Responsible Person

In accordance with Regulation 8, as the responsible person. I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

Signed for and on behalf of Belgotex New Zealand Limited

Glen Ellis

Product Manager

24/11/2023