

Belgotex®

amtico  
first



B.



British  
Excellence

A World of Choice

# amtico first

## Why amtico?

Amtico has been a pioneer of Luxury Vinyl Tile (LVT) flooring for over 50 years, with a reputation built on collaborative creativity, enduring performance, and quality.

Amtico First is a sophisticated collection with a combination of style and function that makes it beautifully versatile for both residential and commercial projects. Easy to work with, specify, lay and maintain plus integrating flawlessly with other materials and designs.



Commercial  
Warranty




Residential  
Warranty



British  
Excellence



In-register  
emboss designs



Natural finish  
with Microbevel



Phthalate  
Free



Made with  
recycled content



100%  
Recyclable




Dutch Oak SF3W2778

# Construction

- Luxury Vinyl Tile
- In-register Emboss
- Plank size 184.2mm x 1219.2mm
- Total thickness 2.0mm
- 12 Year Residential Warranty / 7 Year Commercial Warranty

Amtico First uses the industry's most technically advanced Multiple Performance System giving underfoot comfort and high resistance to wear, resulting in unrivalled durability and a long lasting appearance.



## URETHANE COATING

### HIGH-DENSITY WEAR LAYER

Gives excellent impact resistance and high clarity, with unique realistic embosses and microbevelled edges on each tile and plank.

### PRINT LAYER

Carefully crafted print films create the distinctive Amtico Wood and Stone product designs.

### CORE LAYER

Contains up to 15% recycled pre-consumer content.

### BACKING

The foundation of the product which provides long-lasting stability.



Dry Cedar SF3W2535



**White Oak**  
SF3W2548



**Wheat Oak**  
SF3W2775



**Featured Oak**  
SF3W2533



**Dry Cedar**  
SF3W2535



**Harvest Oak**  
SF3W2774



**Dutch Oak**  
SF3W2778



**Station Oak**  
SF3W2779



**Trent Oak**  
SF3W2777



**Cavalier Oak**  
SF3W5024



**Blackened Oak**  
SF3W2780



White Oak SF3W2548





Wheat Oak SF3W2775



Featured Oak SF3W2533



Dry Cedar SF3W2535



Harvest Oak SF3W2774



Dutch Oak SF3W2778



Station Oak SF3W2779



Trent Oak SF3W2777



Cavalier Oak SF3W5024





**Blackened Oak SF3W2780**

# Accreditations

Recognised around the globe, our environmental accreditations represents the latest and highest standard of environmental impact awareness, operational control and use of materials.



Comparable to Green Guide generic elements 821570039 and 821570066 rated as A+/A.



The CE mark is confirmation by Amtico that our products are in compliance with European health, safety and environmental requirements (as required by Council Directive 89/106/EEC and detailed in EN 14041).



Amtico is a member of the professional association for flexible floor covering manufacturers in Germany.



Amtico International GmbH is a member of the DGNB German Sustainable Building Council.



Our quality system complies with BS EN ISO 9001 and is certified by LRQA.



Recognised around the globe, our BSI accreditation represents the latest and highest standard of environmental impact awareness, operational control and use of materials.



Amtico First products are third-party certified for low-VOC emissions contributing towards good indoor air quality.



SOLS PVC Pro is the French professional organisation of PVC flooring manufacturers; standing for their shared values and commitments related to environment, comfort, regulation and communication.



Phthalate Free

Amtico First products are manufactured using both phthalate-free and bio-based plasticisers except for recycled content.



Amtico First has been certified to achieve the M1 building materials emissions classification for indoor air quality from the Finnish Information Foundation RTS.



Amtico First complies with Indoor Air Comfort Gold version 6.0 and is certified as a low emissions product contributing to a healthy indoor environment.

# Technical Specifications



Commercial  
Warranty




Residential  
Warranty



British  
Excellence



In-register  
emboss designs



Natural finish  
with Microbevel



Phthalate  
Free



Made with  
recycled content



100%  
Recyclable

<b>Construction</b>	Luxury Vinyl Tile
<b>Plank Size</b>	184.2mm x 1219.2mm
<b>Weight</b>	3675g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.3mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	Urethane
<b>Slip Resistance</b>	DS-R10 (DIN 51130 / EN 13893)
<b>Fire Rating</b>	CRF $\geq 11.2 \text{ kW/m}^2$ (ISO 9239-1)
<b>Impact Sound Reduction</b>	3dB (EN ISO 717-2)
<b>Residual Indentation</b>	$\leq 0.1 \text{ mm}$ (ISO 24343-1 / EN 433)
<b>Dimensional Stability</b>	$\leq 0.25\%$ (ISO 23999 / EN 434)
<b>Thermal Insulation</b>	$0.010 \text{ m}^2 \text{ K/W}$ (EN 12664)
<b>Underfloor Heating</b>	Suitable
<b>Curling</b>	$\leq 2 \text{ mm}$ (ISO 23999 / EN 434)
<b>Light Stability</b>	$\geq 6$ (ISO 105 B02)
<b>Resistance to Chemicals</b>	Excellent (EN ISO 26987 / EN 423)
<b>Classifications</b>	Class 23 Domestic Heavy / Class 31 Commercial Light
<b>Warranties</b>	12 Years Residential Warranty / 7 Years Commercial Warranty
<b>Environmental</b>	ISO 14001, A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468)
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

# Care & Maintenance

## DAILY SWEEPING AND DUST MOPPING

- Pick up litter and thoroughly sweep floor area using a dry dust mop.
- Pick up debris with a dustpan and brush.
- Vacuum entrance mats and crevices at all entrances.

## MANUAL MOPPING

Manual mopping is used for soil removal in small or congested areas (including within large floors) and some mark removal. Spray cleaning may be required for heavier surface marking.

- Put out caution signs to warn people that cleaning is in progress.
- Prepare a solution of Amtico Maintainer diluted in accordance with the instructions on the label.
- Using a two-bucket mopping system, apply solution using a damp mop to remove soiling.
- Mop using overlapping strokes.
- Rinse the mop frequently and change the solution as necessary.
- Allow entire floor area to dry thoroughly.
- Remove caution signs.
- Ensure all equipment is cleaned thoroughly after use and stored safely.

## TIPS

- In conditions of heavy soiling, perform a pre-wash by preparing a solution of Amtico Maintainer diluted in accordance with instructions on the container and pre-wash heavily soiled areas.
- Where dirt has become ingrained over time we would recommend that the floor is deep cleaned.
- To help remove stubborn scuff marks use a non abrasive 3M red pad or equivalent.
- Any surface marking that is not removed by routine manual mopping may be removed by occasional spray cleaning.
- Spills of water, grease, food, chemicals and other foreign matter or use of inappropriate cleaning products may cause the floor to become slippery. Wipe up spills immediately with an absorbent cloth, then wash thoroughly with a properly diluted solution of Amtico Maintainer or Spillage Remover until the spill area is completely clean. Rinse and allow to dry thoroughly.
- At least once a year the floor should be scrubbed thoroughly to remove in-grained dirt and floor dressing if applied.

## SPRAY CLEANING

Spray cleaning can be used for light soil removal in small/medium size areas and removal of most scuff marks from all floor sizes. In conditions of heavy soiling, perform a pre-wash by preparing a solution of Amtico Maintainer diluted in accordance with the manufacturer's instructions and pre-wash heavily soiled areas.

- Put out caution signs to warn people that cleaning is in progress.
- Pour a diluted solution of Amtico Maintainer solution in to a suitable spray container.
- Apply a fine mist of liquid on to an area of approximately 2 square metres at a time. Use a rotary buffing machine (approx. 450 rpm) fitted with a red 3M nylon scrubbing pad (or equivalent). Do not buff with any pad more abrasive than a red 3M (or equivalent) pad.
- Work in parallel overlapping passes until the floor is clean and dry.
- Allow entire floor area to dry thoroughly.
- Remove caution signs.
- Ensure all equipment is cleaned thoroughly after use and stored safely.

#### TIPS

- Where dirt has become ingrained over time we would recommend the floor is deep cleaned.
- Spills of water, grease, food, chemicals and other foreign matter or use of inappropriate cleaning products may cause the floor to become slippery. Wipe up spills immediately with an absorbent cloth, then wash thoroughly with a properly diluted Amtico Maintainer or Spillage Remover until the spill area is completely clean. Rinse and allow to dry thoroughly.
- At least once a year the floor should be scrubbed thoroughly to remove in-grained dirt and floor dressing if applied.

## **SCRUBBER DRYING – LARGE AREAS**

Scrubber drying can be used for soil removal in large installations and some mark removal.

- Put out caution signs to warn people that cleaning is in progress.
- Prepare a solution of Amtico Maintainer and pour in to the dispensing tank. The scrubber dryer should be fitted with a red or blue 3M nylon scrubbing pad (or equivalent) or brush.
- Scrub entire floor area.
- Ensure vacuum pick up is operating efficiently.
- Once entire floor area is dry remove caution signs.
- Ensure all equipment is cleaned thoroughly after use and stored safely.

#### TIPS

- Spills of water, grease, food, chemicals and other foreign matter may cause the floor to become slippery. Wipe up spills immediately with an absorbent cloth, then wash thoroughly with a properly diluted solution of Amtico Maintainer until the spill area is completely clean. Rinse and allow to dry thoroughly.
- Any surface marking that is not removed by scrubber drying, may be removed by occasional spray cleaning.
- Soiling in congested areas should be removed using manual mopping.
- At least once a year the floor should be scrubbed thoroughly to remove in-grained dirt and floor dressing if applied.

# Care & Maintenance

## GUIDE TO STRIPPING AND DEEP CLEANING

- Before commencing work, put out caution signs to warn people that cleaning is in progress.
- Sweep floor to remove debris and vacuum entrance mats.
- Prepare a solution of Amtico Stripper using warm water as per instructions on the label.
- Carefully follow all safety instructions, particularly noting that the floor can become slippery during the stripping process.
- Apply plenty of solution over a manageable area using a mop and bucket. Allow 10-15 minutes contact time.
- Agitate the solution using either a low speed rotary machine with a red 3M (or equivalent pad) or with a mop. Edges will need to be agitated manually. Do not allow the slurry to dry.
- Remove slurry with wet vacuum machine or mop and bucket. Rinse floor twice with clean water, allow to dry.
- Remove caution signs.
- Ensure all equipment is cleaned thoroughly after use and stored safely.

## GUIDE TO APPLICATION OF DRESSING

If a protective finish is required or if you are seeking to restore the appearance of an older Amtico tile floor, an application of Amtico Dressing is an option.

Dressings can be applied following stripping of Amtico tile floors. Ensure floor is clean and completely dry prior to applying dressing. Do not use the same equipment for stripping as that used for application of Amtico Dressing.

- Pour a quantity of Amtico Dressing into bucket.
- Load a clean flat applicator mop with dressing.
- Starting at the furthest point from the exit apply a thin even coat around the perimeter and fill in with overlapping passes and allow to dry (for approx 30 minutes in good ventilation).
- Apply a second coat at right angles to the first. Allow to dry.
- Do not buff for 24 hours.
- All equipment should be cleaned thoroughly after use and stored safely.

# Floorcare Starter Kit

The Amtico Floorcare Starter Kit contains what you need to help you make the most of your floor.

- Spillage Remover 500ml
- Maintainer 1 litre
- Protective Felt Pads
- Cleaning Pad

We recommend only using Amtico Maintenance products. Other products may lead to inferior results or leave harmful residues.



**Contact Us:**

P. 0800 377 753

F. 0800 377 754

W. [belgotex.co.nz](http://belgotex.co.nz)



[belgotexNZ](https://www.facebook.com/belgotexNZ)



[belgotex\\_nz](https://www.instagram.com/belgotex_nz)



[belgotex\\_NZ](https://www.pinterest.com/belgotex_NZ)

The colours shown may vary slightly from the actual product and should be used as a guide only.

**Belgotex®**