



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Castor Chair Compatible



R10 Slip Restraint



Construction	Luxury Vinyl Tile
Plank/Tile Size	Various sizes available.
Weight	3561g/m ²
Wear Layer Thickness	0.55mm
Total Thickness	2.5mm
Surface Protection	Urethane
Slip Resistance	≥ 36 in wet, Low potential for slip (BS 7976) DS-R10 (DIN 51130 / EN 13893)
Fire Rating	ISO 9239-1
Impact Sound Reduction	3dB (EN ISO 717-2)
Residual Indentation	≤0.1mm (ISO 24343-1 / EN 433)
Abrasion Resistance	Group T, Type 1 (EN ISO 10582 / EN 649)
Dimensional Stability	≤0.25% (EN ISO 23999, EN 434)
Thermal Insulation	0.013m ² K/W (EN 12664)
Underfloor Heating	Suitable
Curling	≤2mm (EN ISO 23999, EN 434)
Light Stability	6 or better (ISO 105 B02)
Resistance to Chemicals	Excellent (EN ISO 26987 / EN 423)
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranties	10 Year Commercial Warranty
Environmental	ISO 14001, A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.