Les Best

Stain Resistant

Belgotex[®]











~~~~~

Suitable For Stairs







| Construction               | Tufted Saxony Cut Pile Carpet                                                                                                                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Yarn                       | 100% Nylon                                                                                                                                                                                                                                                 |
| Width                      | 4.0m & 5.0m                                                                                                                                                                                                                                                |
| Yarn Weight                | 1200g/m <sup>2</sup> / 35.4oz/yd <sup>2</sup>                                                                                                                                                                                                              |
| Total Weight               | 2200g/m <sup>2</sup>                                                                                                                                                                                                                                       |
| Pile Height                | 6.2mm                                                                                                                                                                                                                                                      |
| Total Thickness            | 8.5mm                                                                                                                                                                                                                                                      |
| Machine Gauge              | 1/10th                                                                                                                                                                                                                                                     |
| Backing                    | Action Back                                                                                                                                                                                                                                                |
| Electrical Properties      | Antistatic                                                                                                                                                                                                                                                 |
| Electrical Propensity      | < 2kV                                                                                                                                                                                                                                                      |
| Fire Rating                | ISO 9239-1                                                                                                                                                                                                                                                 |
| VOC Rating                 | A+ (AgBB protocol and GUT label)                                                                                                                                                                                                                           |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.                                                                                                                                                                                                        |
| Acoustic Insulation        | ΔLw 30dB (ISO 140-8)                                                                                                                                                                                                                                       |
| Acoustic Absorption        | αω 0.20 (ISO 11654)                                                                                                                                                                                                                                        |
| Underfloor Heating         | Suitable                                                                                                                                                                                                                                                   |
| Classification             | Class 33 Commercial Heavy                                                                                                                                                                                                                                  |
| Stair Rating               | Suitable                                                                                                                                                                                                                                                   |
| Warranties                 | <b>10 Year Premium Warranty</b><br>10 Year Residential Wear Warranty<br>10 Year Stain Resistant Warranty<br>10 Year Colourfast Warranty<br>5 Year Manufacturing Defects Warranty<br>10 Year Commercial Wear Warranty                                       |
| Environmental              | Low VOC, 100% Green Electricity, recycled fibre, PVC free<br>ISO 14001, GUT Label, LEED®                                                                                                                                                                   |
| Installation               | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |

For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

