



Construction	Heterogeneous Sheet Vinyl
Width	4.0m
Standard Roll Length	±25m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1800g/m <sup>2</sup>
Wearlayer Thickness	0.35mm
Total Thickness	2.6mm
Surface Protection	PU Lacquer
Slip Resistance	R11 (DIN 51130)
Fire Rating	CRF 6.6kW/m <sup>2</sup> (ISO 9239-1)
Acoustic Insulation	ΔLw 18dB (ISO 717/2)
Thermal Resistance	0.0104W/m/K (EN 12524)
Thermal Insulation	0.25W/m/K (EN 12524)
Chemical Resistance	Very Good (EN ISO 26987)
Underfloor Heating	Suitable
Classifications	Class 23 Domestic Heavy / Class 32 Commercial Medium
Warranties	15 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.