

100%  
Antibacterial100%  
DecontaminationEnvironmentally  
Responsible100%  
Recyclable

Description	Decochoc Protection and Covering Panel
Thickness	2.0mm +/- 0.15mm
Width	1300mm
Length	3000mm
Weight	2800g/m <sup>2</sup> +/-200
Density	1.40g/cm <sup>3</sup>
Hardness	75ShD
Stabilization	CaZn
Surface	Textured with Optimixt Embossment
Thermal Conductivity	0.17 W/(m.K) (DIN 52612)
Fire Rating	B-s2,d0 (EN 13501-1)
Chemicals resistance	Anios compliant H2O2 compliant
Decontamination of surface (radionuclide)	Excellent (ISO 8690)
anti-bacterial activity (2) (S. aureus – S. pyogenes)	> 99% inhibits growth (ISO 22196)
Migration of specific metals	<2 (EN12149-A)
Vinyl Chloride	Non detectable (EN12149-B)
Puncture impact	> 15J (EN ISO 6603-1)
Formaldehyde	Non detectable (EN12149-C)
Impact Resistance Charpy	> 30KJ/m <sup>2</sup> (ISO 179-1)
Indoor Climate	TVOC after 28 days < 15µg/m <sup>3</sup> (ISO 16000-6) A+ Emissions, Greenguard Gold label
Environmental	100% Recyclable REACH
Installation	Please see our website for installation instructions. NB: If the recommended installation is not followed, claims will not be accepted.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.