



Construction	Homogeneous Slip Retardant Sheet Vinyl (Non Phthalate Construction)
Width	2.0m
Standard Roll Length	30.19lm / 60.38m ²
Pattern Repeat	Random Repeat, Reverse Sheet for Seaming
Total Weight	3530g/m ²
Wearlayer Thickness	2.03mm
Total Thickness	2.03mm
Surface Protection	Quantum Guard® HP Urethane Aluminium Oxide Topcoat cured by UV Process
Slip Resistance	Passes wet slip resistance requirements AS/NZS3661.1 and AS/NZS4586 DS-R10 (DIN 51130) Passes - ≥ 0.5 Leather; 0.6 Rubber (ASTM C1028, Dry)
Dynamic Coefficient of Friction	Meets ADA Guidelines (ASTM C1028)
Electrical Propensity	≤ 2kV (EN 1815)
Fire Rating	EN ISO 9239-1: 2010
VOC Rating	SCS Certified – FloorScore Indoor Air Quality Passed and Listed – CHPS 01350 Indoor Air Quality
Underfloor Heating	Suitable up to 32°C
Flexibility	Passes - 11/2" Mandrel - No Crack/Break (ASTM F137)
Static Load	Passes - Residual Indent ≤ 0.005" (ASTM F970) Passes - 2,000 PSI; Residual Indent ≤ 0.005" (ASTM F970 mod.)
Resistance to Light	Passes - < 8 Delta E Color Change (ASTM F1515)
Acoustic	Acoustic IIC - 50 - 6" Concrete with Drop Ceiling (ASTM E492) Acoustic STC - 63 - 6" Concrete with Drop Ceiling (ASTM E90)
Chemical Resistance	Passes - No More Than Slight Change (ASTM F925)
Classification	Extra Heavy Duty Commercial
Warranty	5 Year Commercial Warranty
Environmental	100% Recyclable Environmental Product Declaration NSF / ANSI-332 Gold Certification
Installation	Random Repeat, Reverse Sheet for Seaming Cove fillet is required on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.

