



Stain Resistant



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Anti-Allergenic



Castor Chair Compatible



15 Year Commercial Warranty



GUT Label Certified



LEED Green Building



BREEAM



CRI Green Label Plus



A+ Environmental

Construction	Loop Pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	24pcs / 5.0m <sup>2</sup>
Yarn Weight	520g/m <sup>2</sup>
Total Weight	4020g/m <sup>2</sup>
Pile Height	2.5mm
Total Thickness	5.6mm
Primary Backing	100% Synthetic
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 6.6 kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	22dB (ISO 140-8)
Acoustic Absorption	α <sub>w</sub> 0.15 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	<0.15% m <sup>2</sup> C° /W
Underfloor Heating	Suitable
Colour Fastness	>7/8 on Grey Scale (ISO105-B02)
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GUT Label Certified, LEED®, BREEAM CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001

**Installation** Laying recommendation: Quarter turn.  
Please contact Gilt Edge Industries for all adhesive and installation instructions.  
NB: If recommended adhesive is not used, claims will not be accepted.  
Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.