



Stain Proof



Fade Proof



Environmentally Responsible



Antistatic



Extra Wide
4 Metres



Suitable For
Underfloor Heating



Suitable For
Stairs



Anti-Allergenic



20 Year
Premium
Warranty



Construction	Tufted Patterned Cut Pile Carpet
Yarn	100% Premium Solution Dyed Nylon
Width	4.0m
Standard Roll Length	25m
Yarn Weight	1200g/m ² / 36oz/yd ²
Pile Height	7.0mm
Total Thickness	10.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307 / ISO 6356)
Fire Rating	ISO 9239-1
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
ACCS Grading	REHD2 6 Stars incl. stairs / CHD 3 Stars incl. stairs
Rating	Extra Heavy Duty Residential / Heavy Duty Commercial
Stair Rating	Suitable
Warranties	20 Year Premium Warranty 20 Year Residential Wear Warranty 20 Year Stain Proof Warranty 20 Year Fade Proof Warranty 20 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 10 Year Commercial Wear Warranty
Environmental	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, Eco-Wash™ Treatment, ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.