Berberpoint 920

Belgotex[®]

















Ctain Droot

Fade Resistan

Environmentally

Antistatic

Underfloor Heating

le For Anti-Aller

Construction	Structured needlepunch
Yarn	100% Stainproof Miracle Fibre with recycled content
Width	4.2m
Standard Roll Length	35m
Total Weight	1317g/m²
Total Thickness	7.0mm
Backing	Resinbac
Electrical Properties	Antistatic
Electrical Propensity	<2.0kV - DIN66095 Part 4
Fire Rating	AS/ISO 9239-1
VOC Rating	Pass – GLP Criteria
Stain Resistance	Suitable
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Colour Fastness	7 on Grey Scale - ISO 150-B02
Rating	Heavy Duty Commercial
Warranty	10 Year Needlepunch Warranty
Environmental	Low VOC, Solution dying uses no water, recycled fibre ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.