



Construction	Cut Loop Pile
Yarn	100% Nylon
Size	500mm x 500mm
Tiles per Carton	16pcs / 4.0m ²
Yarn Weight	1030g/m ²
Total Weight	4885g/m ²
Pile Height	5.4mm
Total Thickness	8.5mm
Primary Backing	100% Synthetic
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 6.6 kW/m ² (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	27dB (ISO 140-8)
Acoustic Absorption	αω 0.20 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	<0.15% m ² C° /W
Underfloor Heating	Suitable
Colour Fastness	5-6/8 on Grey Scale (ISO105-B02)
Classification	Class 23 Heavy Duty Residential / Class 32 Medium Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GUT Label Certified, LEED®, BREEAM Green Label Plus Certified Environmental Product Declaration Low VOC, contains recycled fibre ISO 14001

Installation Laying recommendation: Quarter turn or Monolithic.
Please contact Gilt Edge Industries for all adhesive and installation instructions.
NB: If recommended adhesive is not used, claims will not be accepted.
Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.