## Canopy II

## Belgotex<sup>®</sup>























| _               | _              |  |
|-----------------|----------------|--|
|                 |                |  |
| Ctain Desistant | Endo Docistant |  |

| Construction               | Patterned Loop Pile  |
|----------------------------|--|
| Yarn                       | 100% Solution Dyed Nylon   |
| Size                       | 609.6mm x 609.6mm  |
| Tiles per Carton           | 18pcs / 6.7m²  |
| Yarn Weight                | 746g/m²  |
| Pile Height                | 3.0mm  |
| Total Thickness            | 4.7mm  |
| Machine Gauge              | 5/64   |
| Primary Backing            | 100% Synthetic   |
| Secondary Backing          | Infinity Modular   |
| Electrical Properties      | Antistatic   |
| Electrical Propensity      | <3.0kv   |
| Fire Rating                | ISO 9239-1   |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.  |
| Classification             | Heavy Duty Commercial  |
| Stair Rating               | Suitable   |
| Warranty                   | 15 Year Commercial Warranty<br>Limited Lifetime Wear & Backing<br>Limited 15-Year Xguard Stain Resistant<br>Limited 15-Year ColorSafe Bleach Resistant   |
| Environmental              | GreenStar, Homestar™, LEED®  Well Building Standard®  CRI Green Label Plus Certified  Environmental Product Declaration  Contains Recycled content  Low VOC, solution dying uses no water  ISO 14001 |
| Installation               | Laying recommendation: Horizontal Brick Ashlar.  |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.