



<b>Construction</b>	Tufted Multi Hi Low Loop Pile
<b>Yarn</b>	100% Stainproof SDX (Solution Dyed Nylon)
<b>Size</b>	500mm x 500mm
<b>Tiles per Carton</b>	20pcs / 5.0m <sup>2</sup>
<b>Yarn Weight</b>	± 350 g/m <sup>2</sup>
<b>Total Weight</b>	± 3450 g/m <sup>2</sup>
<b>Pile Height</b>	2.0 - 3.5mm
<b>Total Thickness</b>	± 4.5mm
<b>Machine Gauge</b>	1/10th
<b>Backing</b>	Bitumen
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	< 2kV (EN 1307)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Acoustic Insulation</b>	18dB (EN/ISO 10143-3)
<b>Acoustic Absorption</b>	αω 0.15 (EN/ISO 354:2003)
<b>Underfloor Heating</b>	Suitable
<b>Fire Rating</b>	CRF 8.3kW/m <sup>2</sup> (ISO 9239-1)
<b>Fraying Behaviour</b>	Pass (EN 1307)
<b>Dimensional Stability</b>	≤ 0.2% (EN 1307)
<b>Dimensions (Deviations)</b>	0.10% (EN 1307)
<b>VOC Rating</b>	Pass (GBCSA/GBCA)
<b>Colour Fastness</b>	<b>Light</b> 8 (ISO 105 - B02) <b>Rubbing</b> Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) <b>Water</b> 4 - 5 (ISO 105 - E01)
<b>Classification</b>	Heavy Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranty</b>	15 Year Commercial Warranty
<b>Environmental</b>	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, ISO 14001
<b>Installation</b>	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.