



Antistatic



Suitable For Underfloor Heating



Quick & Easy Installation



Easy Clean



Natural Look & Feel



R10 Slip Restraint



Construction	Heterogeneous Sheet Vinyl
Width	2.0m (no selvage edge)
Standard Roll Length	±20m
Pattern Repeat	Refer to Vinyl Range Statement.
Total Weight	2800g/m ²
Wearlayer Thickness	0.70mm
Total Thickness	2.0mm
Surface Protection	Protecsol™
Slip Resistance	R10 (DIN 51 130)
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (EN 1815)
Fire Rating	Bfl-s1 (EN 13501-1)
Dimensional Stability	≤0.04% (EN 434)
Thermal Insulation	0.25W/m/K (EN 12524)
Indoor Air Quality	TVOC after 28 days <100µg/m ³ (ISO 16000-6) Floorscore®
Colour Fastness	≥6° (ISO 105-B02)
Chemical Resistance	Good (EN 423)
Abrasion Resistance	≤2mm ³ (EN 660-2)
Abrasion Group	Group T (EN 649)
Underfloor Heating	Suitable
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranties	10 Year Commercial Warranty
Environmental	REACH Certificate of Compliance ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.