



Stain Resistant



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



Castor Chair Compatible



500 x 500mm



Easy Fit



15 Year Commercial Warranty



Green Label Plus Certification

Construction	Tufted textured loop pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	576g/m <sup>2</sup>
Total Weight	4550g/ m <sup>2</sup>
Pile Height	2.8mm
Total Thickness	5.8mm
Machine Gauge	1/10th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV (ISO 6356)
Fire Rating	CRF 5.9kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	<0.5mg/m <sup>2</sup> /h - Green Label Plus ASTM D5116-06
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	23dB (ISO 140-8)
Acoustic Absorption	α <sub>w</sub> 0.15 (EN ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Castor Chair Resistance	R ≥2.4 (DIN 54324)
Thermal Insulation	0.04m <sup>2</sup> k/W (ISO 8302)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Environmental	Low VOC, solution dyeing uses no water ISO 14001, Green Label Plus Certification
Installation	Laying recommendation: Quarter turn or Brick. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.