## Granite

## Belgotex\*

















Castor Chair









Construction	Patterned Tufted Loop Pile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	± 450g/m²
Total Weight	± 3820 g/m²
Pile Height	2.0mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Backing	EcoBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	28dB (EN ISO 10140)
Acoustic Absorption	αω 0.30 (ISO 354)
Underfloor Heating	Suitable
Fire Rating	CRF 8.6kW/m² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Colour Fastness	Light 7 (ISO 105 - B02)  Rubbing Wet 4 - 5 (ISO 105 - X12)  Dry 4 - 5 (ISO 105 - X12)  Water 4 - 5 (ISO 105 - E01)

- Morning Fog 13.27

  Classification Heavy Duty Commercial
- Stair RatingSuitableWarranty15 Year Commercial Warranty
- **Environmental** GreenStar

Light Reflective Value (LRV)

Low VOC, solution dying uses no water.

2.465.29

5.42

ISO 14001.

Lead

Smoke

Dolphin

- **Installation** Laying recommendation: Monolithic
  - Please contact Gilt Edge Industries for all adhesive and installation instructions.
  - NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

