



Construction	Patterned Tufted Loop Pile	
Yarn	100% Stainproof SDX (Solution Dyed Nylon)	
Size	500mm x 500mm	
Tiles per Carton	20pcs / 5.0m ²	
Pile Weight	± 450g/m ²	
Total Weight	± 3600 g/m ²	
Pile Height	2.0mm	
Total Thickness	6.0mm	
Machine Gauge	1/10th	
Backing	Bitumen	
Electrical Properties	Antistatic	
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)	
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.	
Acoustic Insulation	28dB (EN ISO 10140)	
Acoustic Absorption	α 0.30 (ISO 354)	
Underfloor Heating	Suitable	
Fire Rating	CRF 8.3kW/m ² (ISO 9239-1)	
VOC Rating	Pass (GBCSA/GLP Criteria)	
Colour Fastness	Light	7 (ISO 105 - B02)
	Rubbing	Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12)
	Water	4 - 5 (ISO 105 - E01)
Classification	Heavy Duty Commercial	
Light Reflective Value (LRV)	Midnight	19.2
	Thunder	4.42
	Sunset	4.91
	Horizon	5.17
	Sunrise	5.66
	Cloud Break	9.31
Stair Rating	Suitable	
Warranty	15 Year Commercial Warranty	
Environmental	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water. ISO 14001	
Installation	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.