## Lewis

## Belgotex<sup>®</sup>























Stain Resistant Fade Resistant

stant

Antistatic

Suitable For

Suitable Fo

Castor Chair Compatible

Construction	Tip-Sheared Patterned Loop Pile
Yarn	100% Solution Dyed Nylon
Width	3.81m
Yarn Weight	814g/m²
Pile Height	3.8mm
Total Thickness	7.8mm
Machine Gauge	5/64
Primary Backing	100% Synthetic
Secondary Backing	Integra® HP
Electrical Properties	Antistatic
Electrical Propensity	<3.0kv
Fire Rating	CRF 5.5 kW/m <sup>2</sup> (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	<b>15 Year Commercial Warranty</b> Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant
Environmental	GreenStar, Homestar™, LEED®  Well Building Standard®  CRI Green Label Plus Certified  Environmental Product Declaration  Contains Recycled content  Low VOC, solution dying uses no water  ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.