



Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 4.0m
Standard Roll Length	±30m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1675g/m <sup>2</sup>
Wearlayer Thickness	0.30mm
Total Thickness	2.5mm
Surface Protection	Pureclean
Slip Resistance	R9 (DIN 51130)
Fire Rating	CRF 7.4kW/m <sup>2</sup> (EN 13501-1)
Acoustic Insulation	ΔLw 15dB (ISO 717/2)
Wear Group	T (EN 660-2)
Dimensional Stability	≤0.05% (EN ISO 23999, EN 434)
Thermal Insulation	0.25W/m/K (EN 12524)
Indoor Air Quality	TVOC after 28 days <100µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
Chemical Resistance	Very Good (EN ISO 26987)
Underfloor Heating	Suitable
Residual Indentation	<0.35mm - requirement / 0.20mm - average value measured (EN ISO 24343-2)
Colour Fastness	≥6 (EN 20 105 - B02)
Classifications	Class 23 Domestic Heavy / Class 31 Commercial Light
Warranties	12 Year Residential Warranty
Environmental	Polyester fibers backing with 95% recycled fibres
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.