



Stain Resistant



Fade Resistant



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Castor Chair Compatible



15 Year Commercial Warranty



CRI Green Label Plus



Green Star



Homestar



NSF Certified Environmental Product Declaration



WELL Building Standard

Construction	Tip-Sheared Patterned Loop Pile
Yarn	100% Solution Dyed Nylon
Size	609.6mm x 609.6mm
Tiles per Carton	18pcs / 6.7m ²
Yarn Weight	780g/m ²
Pile Height	3.3mm
Total Height	5.0mm
Machine Gauge	5/64
Primary Backing	100% Synthetic
Secondary Backing	Infinity Modular
Electrical Properties	Antistatic
Electrical Propensity	<3.0kv
Fire Rating	CRF 7.3 kW/m ² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant
Environmental	GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dyeing uses no water ISO 14001
Installation	Laying recommendation: Horizontal Brick Ashlar. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.