Merge

Belgotex[®]





~~~~ Suitable For Underfloor Heating

Å Castor Chair Compatible Suitable For

Stairs



tgreen star



NSF Environ Broduct D WELL

| Construction               | Tip-Sheared Patterned Loop Pile                                                                                                                                                                                                                                                                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Yarn                       | 100% Solution Dyed Nylon                                                                                                                                                                                                                                                                                        |
| Size                       | 457.2mm x 914.4mm                                                                                                                                                                                                                                                                                               |
| Tiles per Carton           | 16pcs / 6.7m²                                                                                                                                                                                                                                                                                                   |
| Yarn Weight                | 814g/m <sup>2</sup>                                                                                                                                                                                                                                                                                             |
| Pile Height                | 3.2mm                                                                                                                                                                                                                                                                                                           |
| Total Height               | 4.9mm                                                                                                                                                                                                                                                                                                           |
| Machine Gauge              | 5/64                                                                                                                                                                                                                                                                                                            |
| Primary Backing            | 100% Synthetic                                                                                                                                                                                                                                                                                                  |
| Secondary Backing          | Infinity Modular                                                                                                                                                                                                                                                                                                |
| Electrical Properties      | Antistatic                                                                                                                                                                                                                                                                                                      |
| Electrical Propensity      | <3.0kv                                                                                                                                                                                                                                                                                                          |
| Fire Rating                | ISO 9239-1                                                                                                                                                                                                                                                                                                      |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.                                                                                                                                                                                                                                                             |
| Classification             | Heavy Duty Commercial                                                                                                                                                                                                                                                                                           |
| Stair Rating               | Suitable                                                                                                                                                                                                                                                                                                        |
| Warranty                   | <b>15 Year Commercial Warranty</b><br>Limited Lifetime Wear & Backing<br>Limited 15-Year Xguard Stain Resistant<br>Limited 15-Year ColorSafe Bleach Resistant                                                                                                                                                   |
| Environmental              | GreenStar, Homestar™, LEED®<br>Well Building Standard®<br>CRI Green Label Plus Certified<br>Environmental Product Declaration<br>Contains Recycled content<br>Low VOC, solution dying uses no water<br>ISO 14001                                                                                                |
| Installation               | Laying recommendation: Verticle Ashlar, Horizontal Brick Ashlar or Monolithic.<br>Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |

■ For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.