



Suitable For Underfloor Heating



Antistatic



Environmentally Responsible



100% Recyclable



P4 / R10 Slip Restraint



12 Year Commercial Warranty



Class 34 Commercial Very Heavy / Class 43 Industrial Heavy



Greentag Certified



Construction	Homogeneous Sheet Vinyl
Width	2.0m
Standard Roll Length	20m / 40m <sup>2</sup>
Pattern Repeat	Random repeat, directional laying.
Total Weight	2850g/m <sup>2</sup>
Wearlayer Thickness	2.0mm
Total Thickness	2.0mm
Surface Protection	Evercare™
Slip Resistance - Wet Pendulum	P4 (AS 4586:2013, App A)
Slip Resistance - Oil Wet Ramp	R10 (AS 4586:2004 App D)
Electrical Propensity	<2kV (EN 1815)
Fire Rating	CRF 9.9kW/m <sup>2</sup> (ISO 9239-1)
Acoustic Insulation	5dB (ISO 717-2)
Wear Resistance	~0.02mm (EN 660.2)
Wear Group	T (NF 189)
Type Binder Content	I (EN ISO 10581)
Dimensional Stability	≤0.40% (ISO 23999, EN 434)
Thermal Insulation	0.25W/mK (EN ISO 10456, EN 12524)
Indoor Air Quality	TVOC after 28 days <10µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
Anti-bacterial Activity (E. coli - S. aureus - MRSA)	> 99% inhibits growth (ISO 22196)
Residual Indentation	~0.02mm (EN ISO 24343-1, EN 433)
Colour Fastness	≥6 (EN 20 105 - B02)
Chemical Resistance	OK (EN ISO 26987, EN 423)
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranty	12 Year Commercial Warranty
Environmental	100% Recyclable Environmental Product Declaration Greentag Certified
Installation	Random Repeat, Reverse Sheet for Seaming Cove fillet is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.