



Suitable For Underfloor Heating



Antistatic



Environmentally Responsible



100% Recyclable



P4 / R10 Slip Restraint



12 Year Commercial Warranty



<b>Construction</b>	100% Bio-based Plasticier Homogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	20m / 40m <sup>2</sup>
<b>Pattern Repeat</b>	Random repeat, directional laying.
<b>Total Weight</b>	2580g/m <sup>2</sup>
<b>Wearlayer Thickness</b>	2.0mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	Evercare™
<b>Slip Resistance - Wet Pendulum</b>	P4 (AS 4586-2013, App A)
<b>Slip Resistance - Oil Wet Ramp</b>	R10 (AS/NZS 4586:2004, App D)
<b>Electrical Propensity</b>	<2kV (EN 1815)
<b>Fire Rating</b>	CRF 9.4kW/m <sup>2</sup> (ISO 9239-1)
<b>Acoustic Insulation</b>	5dB (ISO 717-2)
<b>Wear Resistance</b>	≤2mm <sup>3</sup> (EN 660.2)
<b>Wear Group</b>	T (NF 189)
<b>Type Binder Content</b>	I (EN ISO 10581)
<b>Dimensional Stability</b>	≤0.40% (ISO 23999, EN 434)
<b>Thermal Insulation</b>	0.25W/mK (EN ISO 10456, EN 12524)
<b>Indoor Air Quality</b>	TVOC after 28 days <10µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
<b>Anti-bacterial Activity (E. coli - S. aureus - MRSA)</b>	> 99% inhibits growth (ISO 22196)
<b>Residual Indentation</b>	~0.02mm (EN ISO 24343-1, EN 433)
<b>Colour Fastness</b>	≥6 (EN 20 105 - B02)
<b>Chemical Resistance</b>	OK (EN ISO 26987, EN 423)
<b>Classifications</b>	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
<b>Warranty</b>	12 Year Commercial Warranty
<b>Environmental</b>	100% Recyclable Environmental Product Declaration Greentag Certified
<b>Installation</b>	Random Repeat, Reverse Sheet for Seaming Cove fillet is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.