



| | |
|----------------------------|---|
| Construction | Textured Patterned Loop Pile |
| Yarn | 100% Solution Dyed Nylon |
| Size | 609.6mm x 609.6mm |
| Tiles per Carton | 18pcs / 6.7m ² |
| Yarn Weight | 814g/m ² |
| Pile Height | 3.4mm |
| Total Thickness | 5.1mm |
| Machine Gauge | 5/64 |
| Primary Backing | 100% Synthetic |
| Secondary Backing | Infinity Modular |
| Electrical Properties | Antistatic |
| Electrical Propensity | <3.0kv |
| Fire Rating | CRF 7.9 kW/m ² (ISO 9239-1) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Classification | Heavy Duty Commercial |
| Stair Rating | Suitable |
| Warranty | 15 Year Commercial Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant |
| Environmental | GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dyeing uses no water ISO 14001 |
| Installation | Laying recommendation: Monolithic. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.