



Construction	Tufted Textured Loop Pile Carpet
Yarn	Stainproof Solution Dyed Nylon Blend
Width	4.0m
Standard Roll Length	35m
Yarn Weight	1055g/m ² / 31oz/yd ²
Total Weight	2050g/m ²
Pile Height	9.0mm
Total Thickness	10.0mm
Machine Gauge	5/16"
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307 / ISO 6356)
Fire Rating	CRF 4.9kW/m ² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GBCA Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
Rating	Extra Heavy Duty Residential / Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Textured Warranty 15 Year Residential Wear Warranty 20 Year Stain Proof Warranty 20 Year Fade Proof Warranty 20 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 7 Year Commercial Wear Warranty
Environmental	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.