## Origami

## Belgotex<sup>®</sup>



























(-	<i>æ)</i>	
(	<del>'</del> )	

Stain Resistant Fade Resistant

Responsible

Antistatic

Suitable For

Suitable For

Anti-Allergenic

Castor Chair

Construction	Tufted patterned loop pile
Yarn	100% Polyamide
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Yarn Weight	580g/m²
Total Weight	4090g/m²
Pile Height	2.4mm
Total Thickness	5.7mm
Machine Gauge	1/10th
Primary Backing	Non-woven PVC free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	< 2kV
Fire Rating	EN ISO 9239-1
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	22dB
Acoustic Absorption	αω 0.15
Dimensional Stability	<0.20% - EN986
Thermal Insulation	<0.17% m <sup>2</sup> C°/W
Underfloor Heating	Suitable
Colour Fastness	5-6/8 on Grey Scale – ISO105-B02
Stain Resistance	Invista anti-soil and anti-microbial treatment / 4 - ASTM D6540-00
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GUT Label Certified, CRI Green Lebl Certified Low VOC, 100% Green Electricity, PVC free ISO 14001, GUT Label
Installation	Laying recommendation: Quarter turn mandatory.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.