Peak To Marble - Scope HD

Belgotex[®]



























Stain Resistant Fade Resistant

Antistatic

Suitable For

Construction	Structured Loop Pile
Yarn	100% Regenerated Solution Dyed ECONYL Nylon
Size	500mm x 500mm
Tiles per Carton	16pcs / 4.0m ²
Yarn Weight	1050g/m ²
Total Weight	5210g/m ²
Pile Height	5.0mm
Total Thickness	9.7mm
Machine Gauge	1/10
Primary Backing	Non-Woven PVC Free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	BfI-S1 (EN 14041)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	27dB (ISO 140-8)
Acoustic Absorption	αω 0.25 (ISO 11654)
Dimensional Stability	≤0.20% (EN 986)
Thermal Insulation	<0.17%m²C°/W
Underfloor Heating	Suitable
Colour Fastness	>7/8 on Grey Scale
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

