



Construction	Structured loop pile
Yarn	100% Regenerated Solution Dyed Econyl Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	580g/m <sup>2</sup>
Total Weight	4200g/m <sup>2</sup>
Pile Height	2.6mm
Total Thickness	5.8mm
Primary Backing	Non-woven PVC free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 6.6kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	26dB (ISO 140-8)
Acoustic Absorption	α <sub>w</sub> 0.15 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	<0.17% <sup>m<sup>2</sup>C</sup> /W
Underfloor Heating	Suitable
Colour Fastness	>7/8 on Grey Scale (ISO105-B02)
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.