



Stain Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	4.0m
Pattern Repeat	± W 9cm x L 135cm
Yarn Weight	1250g/m <sup>2</sup> / 36.8oz/yd <sup>2</sup>
Total Weight	2670g/m <sup>2</sup>
Pile Height	6.3mm
Total Thickness	10mm
Machine Gauge	1/10th
Backing	Action Back
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 8.5kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Impact Sound Insulation	ΔLw 30 dB (ISO 140-8)
Sound Absorption	α <sub>w</sub> 0.25 (ISO 11654)
Underfloor Heating	Suitable
Classifications	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Environmental	GUT Label LEED® Low VOC, ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.