



Stain Proof



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



5 Year Needle Punch Warranty



REACH

Construction	Ribbed needlepunch carpet
Yarn	100% Stainproof Miracle Fibre
Width	2.0m
Standard Roll Length	30m
Yarn Weight	900g/m ²
Total Thickness	9.0mm
Backing	Resinbac
Electrical Properties	Antistatic
Fire Rating	ISO 9239-1
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
UV Fade Resistance	5000 hours UV stabilized fibre
Use	Indoor / Outdoor
Rating	Extra Heavy Duty Commercial
Warranty	5 Year Needlepunch Warranty
Environmental	REACH Compliant Low VOC, solution dyeing uses no water ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.