



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Anti-Allergenic



2 Year NeedlePunch Warranty



REACH

Construction	Finely ribbed needlepunch carpet
Yarn	100% Solution Dyed Olefin
Width	2.0m
Standard Roll Length	50m
Yarn Weight	250g/m <sup>2</sup> / 24.3oz/yd <sup>2</sup>
Total Weight	500g/m <sup>2</sup>
Pile Height	1.5mm
Total Thickness	4.0mm
Backing	Foam Back
Electrical Properties	Antistatic
Use	Indoor
Rating	Residential
Warranty	2 Year Needlepunch Warranty
Environmental	REACH Compliant Low VOC, solution dyeing uses no water ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.