



| | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction | Loop Pile |
| Yarn | 100% Regenerated Solution Dyed ECONYL Nylon |
| Size | 500mm x 500mm |
| Tiles per Carton | 20pcs / 5.0m ² |
| Yarn Weight | 620g/m ² |
| Total Weight | 4105g/m ² |
| Pile Height | 3.2mm |
| Total Thickness | 6.5mm |
| Machine Gauge | 1/10 |
| Primary Backing | Non-Woven PVC Free |
| Secondary Backing | Bitumen |
| Electrical Properties | Antistatic |
| Electrical Propensity | ≤ 2kV |
| Fire Rating | CRF 8.3kW/m ² (ISO 9239-1) |
| VOC Rating | A+ (AgBB protocol and GUT label) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Acoustic Insulation | 26dB (ISO 140-8) |
| Acoustic Absorption | αω 0.20 (ISO 11654) |
| Dimensional Stability | <0.20% (EN 986) |
| Thermal Insulation | <0.15% ^{m²C} /W |
| Underfloor Heating | Suitable |
| Colour Fastness | >7/8 on Grey Scale |
| Classification | Class 33 Commercial Heavy |
| Stair Rating | Suitable |
| Warranty | 15 Year Commercial Warranty |
| Environmental | GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001 |
| Installation | Laying recommendation: Monolithic or Brick. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.