



Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 4.0m
Standard Roll Length	±32m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1200g/m <sup>2</sup>
Wearlayer Thickness	0.15mm
Total Thickness	2.0mm
Surface Protection	PU Lacquer
Slip Resistance	R10 (DIN 51130)
Fire Rating	Bfl -s1 (EN 13501)
Acoustic Insulation	ΔLw 10dB (ISO 717/2)
Dimensional Stability	≤0.40% (EN ISO 23999)
Thermal Resistance	0.015m <sup>2</sup> K/w (ISO 8302)
Thermal Insulation	0.13W/m/K (EN 12524)
Residual Indentation	≤0.35mm (EN ISO 24343-1)
Indoor Air Quality	FloorScore®, A+ Emissions
Chemical Resistance	Resistant (EN ISO 26987)
Light Fastness	≥6 (EN ISO 105 B02)
Underfloor Heating	Suitable
Classifications	Class 21 Domestic Light
Warranties	5 Year Residential Warranty
Environmental	100% Phthalate Free, 100% Recyclable ISO 14001, ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.