Reform Artworks Angle • Assemble • Connect

Belgotex[®]







Suitable For Anti-Allergenic Stairs

¥



Compatible





Construction	Structured Loop Pile
Yarn	100% Regenerated Econyl Millitron Dyed Nylon
Size	480mm x 480mm (960mm x 960mm available indent)
Tiles per Carton	20pcs / 4.608m ²
Yarn Weight	650g/m ²
Total Weight	2700g/m ²
Pile Height	3.0mm
Total Thickness	8.0mm
Primary Backing	Non-woven PVC free
Secondary Backing	Ecotrust 350 acoustic, 100% recycled
Electrical Properties	Antistatic
Electrical Propensity	≤2kV
Fire Rating	CRF 5.2kW/m ² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	26dB (ISO 717-2)
Acoustic Absorption	αω 0.25 (ISO 354)
Dimensional Stability	<0.20% (EN 986)
Underfloor Heating	Suitable (approx. 0.13m²k/W)
Colour Fastness	>5 on Grey Scale (ISO 105-B02)
Classification	Class 33 Commercial Heavy
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	10 Year Commercial Wear Warranty
Environmental	Low VOC, recycled fibre, PVC free Cradle to Cradle Certified (Bronze), LEED® 100% recycled backing
Installation	Laying recommendation: Monolithic or Quarter Turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

■ For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.