



Construction	Loop Pile
Yarn	100% Regenerated ECONYL Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	770g/m <sup>2</sup>
Total Weight	4365g/m <sup>2</sup>
Pile Height	3.4mm
Total Thickness	6.8mm
Machine Gauge	1/12
Primary Backing	Non-Woven PVC Free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 8.3kW/m <sup>2</sup> (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	25dB (ISO 140-8)
Acoustic Absorption	α <sub>w</sub> 0.20 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	<0.15% m <sup>2</sup> C° /W
Underfloor Heating	Suitable
Colour Fastness	5-6/8 on Grey Scale
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001
Installation	Laying recommendation: Monolithic or Brick. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.