## Rossetti 2

## Belgotex<sup>®</sup>























| $\sim$          | $\sim$         |  |
|-----------------|----------------|--|
| Stain Decistant | Fade Desistant |  |

Castor Chair

| Construction               | Patterned Loop Pile   |
|----------------------------|---|
| Yarn                       | 100% Solution Dyed Nylon  |
| Width                      | 3.81m   |
| Yarn Weight                | 814g/m²   |
| Pile Height                | 3.4mm   |
| Total Thickness            | 7.4mm   |
| Machine Gauge              | 5/64  |
| Primary Backing            | 100% Synthetic  |
| Secondary Backing          | Integra® HP   |
| Electrical Properties      | Antistatic  |
| Electrical Propensity      | <3.0kv  |
| Fire Rating                | CRF 4.5 kW/m <sup>2</sup> (ISO 9239-1)  |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.   |
| Classification             | Heavy Duty Commercial   |
| Stair Rating               | Suitable  |
| Warranty                   | 15 Year Commercial Warranty<br>Limited Lifetime Wear & Backing<br>Limited 15-Year Xguard Stain Resistant<br>Limited 15-Year ColorSafe Bleach Resistant  |
| Environmental              | GreenStar, Homestar™, LEED®  Well Building Standard®  CRI Green Label Plus Certified  Environmental Product Declaration  Contains Recycled content  Low VOC, solution dying uses no water ISO 14001 |
| Installation               | Please contact Gilt Edge Industries for all adhesive and installation instructions.   |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.