School

Belgotex[®]





















Environmentally Responsible

Antistatic

Suitable For Underfloor Heating

Construction	Loop Pile Scroll Carpet
Yarn	100% Solution Dyed Nylon
Width	3.66m
Standard Roll Length	35m
Pattern Repeat	L: 30cm x W: 69.5cm
Yarn Weight	500g/m ²
Total Weight	1500g/m²
Pile Height	2.0mm - 4.0mm
Total Thickness	6.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	Action Back
Electrical Properties	Antistatic
Fire Rating	ASTM E 648-10
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential / Heavy Duty Commercial
Stair Rating	Suitable
Warranties	10 Year Commercial Warranty 10 Year Residential Wear Warranty 10 Year Stain Resistant Warranty 10 Year Fade Resistant Warranty 10 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 10 Year Commercial Wear Warranty
Environmental	Low VOC, solution dying uses no water CRI Green Label Plus ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

