Schubert

Belgotex[®]



Antistatio





star



WELL

Stain Resistant Fade Resistant

Suitable For Underfloor Heating

Stairs

Compatible

	*	homes
--	---	-------



Construction Patterned Loop Pile Yarn 100% Solution Dyed Nylon Width 3.81m Yarn Weight 814g/m² Pile Height 3.4mm Total Thickness 7.4mm 5/64 Machine Gauge 100% Synthetic **Primary Backing** Secondary Backing Integra® HP **Electrical Properties** Antistatic **Electrical Propensity** <3.0kv CRF 4.5 kW/m² (ISO 9239-1) Fire Rating Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew. Classification Heavy Duty Commercial Stair Rating Suitable 15 Year Commercial Warranty Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant Environmental GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dying uses no water ISO 14001 Installation Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.