



Construction	Loop Pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	24pcs / 6.0m ²
Yarn Weight	540g/m ²
Total Weight	3955g/m ²
Pile Height	2.3mm
Total Thickness	5.5mm
Machine Gauge	1/10
Primary Backing	Non-Woven PVC Free
Secondary Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 8.0kw/m ² (ISO 9239-1)
VOC Rating	A+ (AgBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	24dB (ISO 140-8)
Acoustic Absorption	α _w 0.15 (ISO 11654)
Dimensional Stability	≤0.20% (EN 986)
Thermal Insulation	<0.15m ² C° /W
Underfloor Heating	Suitable
Colour Fastness	>7/8 on Grey Scale
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	Gut Label Certified, LEED® CRI Green Label Certified Low VOC, 100% In Face Fiber Contains recycled content 100% Green Electricity ISO 14001
Installation	Laying recommendation: Monolithic, Brick or Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.