Select Plus

Belgotex[®]



Underfloor Heating









Indoor Air





Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 3.0m
Standard Roll Length	35m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1400g/m ²
Wearlayer Thickness	0.2mm
Total Thickness	1.7mm
Surface Protection	Natural Feel
Slip Resistance	DS-R10 (DIN51130)
Fire Rating	ISO 9239-1
Acoustic Insulation	16dB (ISO717)
Thermal Insulation	0.25W/mK (EN12524)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Chemical Resistance	Very Good (EN ISO26987)
Classification	Class 22 Domestic Medium
Warranty	5 Year Residential Warranty
Environmental	REACH Certificate of Compliance ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

■ For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.

Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

• Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.