Stock Brights

Belgotex[®]























| 0 | - | ı | n | n | a | ti | b | ı | e |
|---|---|---|---|---|---|----|---|---|---|
| | | | | Г | | | | | |

| Construction | Textured Patterned Loop Pile | | | | |
|----------------------------|--|--|--|--|--|
| Yarn | 100% Solution Dyed Nylon | | | | |
| Size | 609.6mm x 609.6mm | | | | |
| Tiles per Carton | 18pcs / 6.7m ² | | | | |
| Yarn Weight | 576g/m² | | | | |
| Pile Height | 3.1mm | | | | |
| Total Thickness | 7.1mm | | | | |
| Machine Gauge | 1/10 | | | | |
| Primary Backing | 100% Synthetic | | | | |
| Secondary Backing | Infinity Modular | | | | |
| Electrical Properties | Antistatic | | | | |
| Electrical Propensity | <3.0kv | | | | |
| Fire Rating | CRF 6.9 kW/m ² (ISO 9239-1) | | | | |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. | | | | |
| Classification | Heavy Duty Commercial | | | | |
| Stair Rating | Suitable | | | | |
| Warranty | 15 Year Commercial Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant | | | | |
| Environmental | GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dying uses no water ISO 14001 | | | | |
| Installation | Laying recommendation: Horizontal Brick Ashlar Only. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards. | | | | |
| | | | | | |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.