



Suitable For Underfloor Heating



Antistatic



Environmentally Responsible



100% Recyclable



R11 Slip Restraint



12 Year Commercial Warranty



floor score



Greentag Certified



Construction	Multi-Layered Sheet Vinyl
Width	2.0m
Standard Roll Length	20m / 40m ²
Pattern Repeat	Random repeat, directional laying.
Total Weight	2400g/m ²
Wearlayer Thickness	1.0mm
Total Thickness	2.0mm
Slip Resistance - Dry & Wet Pendulum	P3 (AS 4586: 2013, App A), >36PTV (BS 7976-2)
Slip Resistance - Oil Wet Ramp	R11 (DIN 51130)
Slip Resistance - Wet Bare Foot	C (DIN 51097)
Slip Resistance - Ramp Test	ESb (EN 13845 / annex C)
Slip Resistance - Wet Areas	3 (CTE)
Surface Roughness	Rz >20 µm (UK slip resistant group)
Electrical Propensity	<2kV (EN 1815)
Fire Rating	CRF 6.2kW/m ² (ISO 9239-1)
Wear Resistance	≤4mm ³ (EN 660.2)
Wear Group	P (EN 649)
Type Binder Content	I (EN ISO 10582)
Dimensional Stability	≤0.40% (EN 434)
Thermal Insulation	0.25W/mK (EN 12524)
Indoor Air Quality	TVOC after 28 days <100µg/m ³ (ISO 16000-6) FloorScore®
Antimicrobial	> 99% inhibits growth (ISO 22196)
Residual Indentation	≤0.10mm (EN 433)
Colour Fastness	≥6 (EN 20 105 - B02)
Chemical Resistance	OK (EN 423)
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranty	12 Year Commercial Warranty
Environmental	100% Recyclable, Greentag Certified
Installation	Random Repeat, Reverse Sheet for Seaming Cove fillet is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.