Terrain

Belgotex[®]



















500 x 500mm







Construction	Tufted Loop Pile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	1000mm x 250mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	± 500g/m²
Total Weight	± 3897g/m²
Pile Height	± 3.0mm
Total Thickness	± 6.0mm
Machine Gauge	1/10th
Backing	EcoBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Absorption	αω 0.15 (ISO 354)
Underfloor Heating	Suitable
Fire Rating	CRF 8.6kW/m² (ISO 9239-1)
VOC Rating	Pass
Colour Fastness	Light 7 (ISO 105 - B02) Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) Water 4 - 5 (ISO 105 - E01)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar Low VOC, solution dying uses no water. ISO 14001
Installation	Laying recommendation: Parquet or brick.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

