



DECOTREND



▶ TREND EFFECT DECORATIVE PROTECTION PANEL

Applications

This range of panels uplifts and highlights interiors in an original manner and fits into a modern and urban design. The product can be thermoformed for use on round pillars (diameter under 800 mm) and to ensure a perfect hygiene in the angles. Their high degree of strength is useful for covering walls of bedrooms, reception areas and dining areas in hotels, retirement homes, schools or any form of establishment open to the public.

Description

- Model: Decotrend decorative protection panel
- Standard panel dimensions: 3 m x 1.30 m
- Thickness: 2 mm
- Material: trend decor Bs2d0 fire-rated PVC
- Surface finish: metalized or concrete effect
- Fixing: adhesive bonding with SPM acrylic glue or SPM universal mastic glue. Joints between panels can be made using silicone joints or PVC welding rods, colour matched to the range.
- Colours: 4 standard trend decors

Specification

- Description : 2 mm thick trend effect decorative protection panel (Decotrend as manufactured by SPM - Composite or Brushed Aluminium or Concrete) from rigid metalized or concrete effect PVC achieving Bs2d0 fire rating and impact and scratch resistance. A protective film is specified to minimise cleaning before acceptance. 3.00 long, 1.30 high.
- Environment: no heavy metals and no substance potentially subjected to any REACH restriction are used in its manufacture, nor PBT/BPA. The calcium-zinc thermal stabilisation process is used. The emission level of volatile substance in inside air has been tested according to ISO 16000-6 and is very low (A+) according to the French regulation (23 March 2011 nr 2011-321 Decree and 19 April 2011 Order). 100% of the product are recyclable.
- Colour: selected by architects from manufacturer's standard range.
- Installation method: glue as per manufacturer's instructions.

