Zéphir

Belgotex[®]

























Construction

Tiles per Carton Yarn Weight

Yarn Size

Stain Resistant Fade Resistant Environmentally

Responsible

Antistatio

Suitable For Underfloor Heating

Loop Pile

Suitable For

Anti-Allergenic

100% Regenerated Solution Dyed ECONYL Nylon
500mm x 500mm
20pcs / 5.0m ²
620g/m ²

Total Weight 4105g/m² Pile Height 3.2mm **Total Thickness** 6.5mm Machine Gauge 1/10

Non-Woven PVC Free **Primary Backing**

Secondary Backing Bitumen **Electrical Properties** Antistatic **Electrical Propensity** ≤ 2kV

Fire Rating BfI-S1 (EN 13501-1)

VOC Rating A+ (AgBB protocol and GUT label)

Will not shed or pill. Resistant to mould & mildew. Anti-allergenic Properties

26dB (ISO 140-8) **Acoustic Insulation** Acoustic Absorption αω 0.20 (ISO 11654) <0.20% (EN 986) **Dimensional Stability**

Thermal Insulation $<0.17\%m^2C^{\circ}/W$ Suitable **Underfloor Heating**

Colour Fastness >7/8 on Grey Scale

Classification Class 33 Commercial Heavy

Stair Rating Suitable

Warranty 15 Year Commercial Warranty

Environmental Low VOC, 100% Green Electricity,

Recycled Fibre

PVC free, ISO 14001, GUT Label, LEED®

Installation Laying recommendation: Monolithic.

Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

