

Copenhagen



Construction	Tufted Loop Pile Carpet
Yarn	100% Wool
Yarn Specification	4 & 2-ply yarn, stock dyed
Width	4.0m
Standard Roll Length	30m
Yarn Weight	1100g/m ² / 32oz/yd ²
Total Weight	2450g/m ²
Pile Height	5.7mm
Total Thickness	9.3mm
Machine Gauge	1/4"
Primary Backing	Synthetic woven fabric
Secondary Backing	Jute
Electrical Properties	Antistatic
Fire Rating	Cfl-s1 (EN 13501)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Rating	Heavy Duty Residential Light Duty Commercial
Stair Rating	Suitable
Warranties	10 Year Residential Warranty 5 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Certified, Low VOC, EN 14041 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices