

EUROPEAN HARDENED TIMBER FLOORING BPIR DECLARATION

Designated Building Product: **Class 1**

Version 2.0 July 2025

Declaration

Belgotex New Zealand Ltd (Belgotex NZ) has provided this declaration to satisfy the provisions of the [Building \(Building Product Information Requirements\) Regulations 2022](#).

Company Details

Name	Belgotex New Zealand Limited
Role	Supplier
NZBN	9429038353000
Address	25 Leslie Hills Drive, Riccarton, Christchurch 8011
Website	www.belgotex.co.nz
Email	info@belgotex.co.nz
Phone	0800-377-753

Description of Building Product

Belgotex NZ supplies a range of [Parky European Hardened Timber Flooring products](#).

Parky European Hardened Timber Flooring is a modular, multi-layered timber floorcovering composed of a lacquer coated wood veneer top layer adhered to a High-Density Fibreboard (HDF) core with real wood backing.

Parky European Hardened Timber Flooring has a watertight click joint system and can be installed as a floating floor or directly adhered to the subfloor.

When installed, Parky European Hardened Timber Flooring may contribute to G6 (Airborne and impact sound) or H1 (Energy efficiency) requirements. Compliance with these requirements needs to be established as part of the proposed flooring system.

Parky European Hardened Timber Flooring is supplied in plank format and sold by the square metre.

Building Code Obligations

When installed in accordance with Parky installation requirements, Parky European Hardened Timber Flooring may contribute to compliance with the applicable performance criteria under the following Building Code clauses.

Building Code Clause	Contribution to Compliance
B2 (Durability) B2.3.1(c)	Durability under heavy duty residential and commercial use has been established through evaluation to EN 14354. Parky European Hardened Timber Flooring has been supplied and installed in buildings in Europe for over 5 years, demonstrating a good track record of in-service performance.
C3 (Fire affecting areas beyond the fire source) C3.4(b)	A Critical Radiant Flux (CRF) of $\geq 4.5 \text{ kW/m}^2$ has been determined through testing to ISO 9239-1. Parky European Hardened Timber flooring can be used in all building areas and all risk groups.
D1 (Access routes) D1.3.3 (d)	Parky European Hardened Timber flooring has an acceptable slip resistance—as per D1/AS1 Table 2—when used in level access routes expected to remain dry under normal use.

**EUROPEAN HARDENED TIMBER FLOORING
BPIR DECLARATION**

	Slip Resistance Value (SRV) of 57 and P5 rating have been determined through testing using the wet pendulum test method of AS 4586 Appendix A. Parky European Hardened Timber flooring is acceptable for use in level access routes expected to become wet with water in normal use and on stairs and ramps not steeper than 1:12.
E3 (Internal moisture) E3.3.3 E3.3.5 E3.3.6	Parky European Hardened Timber flooring meets the requirement for impervious and easily cleaned floor surfaces in watersplash areas such as kitchens, laundries, and toilets. Imperviousness of the Parky European Hardened Timber flooring surface and junction has been demonstrated through moisture resistance testing to ISO 4760:2022 when installed floating or glued directly to the substrate.
F2 (Hazardous building materials) F2.3.1	Low emission of volatile organic compounds (VOC) has been established through FloorScore certification.

Scope of use and Limitations

Scope	Limitation
For building areas with up to heavy commercial level of use	<ul style="list-style-type: none"> • Parky European Hardened Timber flooring is for interior use only. • Subfloors must be stable and able to structurally support the flooring. • Concrete substrate must have a relative humidity of 75% or below. • Flooring must be laid in accordance with Parky Installation Instructions.
For use in wet areas (bathrooms, toilets, laundries, kitchens)	<ul style="list-style-type: none"> • Parky European Hardened Timber flooring is suitable for use within 1.5 metres of a sanitary fixture or appliance. • Flooring must be installed according to the instructions for wet areas detailed in the Parky Installation Instructions. • Flooring is not recommended for use in bathrooms.
For use in access routes	<ul style="list-style-type: none"> • Parky European Hardened Timber flooring is suitable for use in access routes.
In connection with underfloor heating including in-slab piped water heating.	<ul style="list-style-type: none"> • Parky European Hardened Timber flooring is suitable for use with underfloor heating not exceeding 27°C.

Conditions of use

Parky European Hardened Timber Flooring must be installed according to the Parky Installation Instructions and maintained according to the Parky Care & Maintenance guidelines available at www.belgotex.co.nz.

Additional Information

For all specification, installation, maintenance and warranty information, and all information supporting Belgotex NZ claims, refer to www.belgotex.co.nz.

Responsible Person

**EUROPEAN HARDENED TIMBER FLOORING
BPIR DECLARATION**

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm Parky European Hardened Timber Flooring, as referred to in this statement, is not subject to a warning or ban issued under [Section 26 of the Building Act](#).

Signed for and on behalf of Belgotex New Zealand Limited

Jeremy Parish

Managing Director

15/07/2025