

Belgotex®

GTI MAX INTERLOCKING VINYL TILES

BPIR DECLARATION



Designated Building Product: **Class 1**

Version 1.0 November 2025

Declaration

Belgotex New Zealand Ltd (Belgotex NZ) has provided this declaration to satisfy the provisions of the [Building \(Building Product Information Requirements\) Regulations 2022](#).

Company Details

Name	Belgotex New Zealand Limited
Role	Supplier
NZBN	9429038353000
Address	25 Leslie Hills Drive, Riccarton, Christchurch 8011
Website	www.belgotex.co.nz
Email	info@belgotex.co.nz
Phone	0800-377-753

Description of Building Product

Belgotex NZ supplies GTI MAX Interlocking Vinyl Tiles for installation and use in heavy traffic commercial and industrial environments such as retail spaces, supermarkets, production facilities, and storage areas. The tiles are manufactured by [Gerflor](#).

GTI MAX Interlocking Vinyl Tiles are a resilient flooring made from Polyvinyl Chloride (PVC) resin. Each tile features a multi-layered construction that includes a PUR surface treatment, a homogeneous PVC wear layer, and interlayers reinforced with glass-fibre grids. These layers are fused under high heat and pressure to form a durable, multi-material structure. The tiles are supplied in an interlocking format for easy, loose-lay installation.

GTI MAX Interlocking Vinyl Tiles are 6mm thick and measure 635mm x 635mm. Each tile comes with dovetail joints for secure installation.

Belgotex NZ supplies accessories—ramping, coving, and edging—that are integral to the installation system and are covered under this declaration.

When installed, GTI MAX Interlocking Vinyl Tiles may contribute to G6 (Airborne and impact sound). Compliance with this requirement needs to be established as part of the proposed flooring system.

Building Code Obligations

When installed in accordance with Belgotex NZ installation requirements, GTI MAX Interlocking Vinyl Tiles may contribute to compliance with the applicable performance criteria under the following Building Code clauses.

Building Code Clause	Contribution to Compliance
B2 (Durability) B2.3.1(c)	Durability under commercial use has been established through evaluation to EN 14041. GTI MAX Interlocking Vinyl Tiles have been reliably supplied and installed in buildings in New Zealand for over 5 years, demonstrating a strong track record of in-service performance.
C3 (Fire affecting areas beyond the fire source) C3.4(b)	A Critical Radiant Flux (CRF) value of 9.3 kW/m ² has been determined through testing to ISO 9239-1:2010. GTI MAX Interlocking Vinyl Tiles can be used as flooring in all building areas and all risk groups.
D1 (Access routes) D1.3.3(d)	GTI MAX has acceptable slip resistance—as per D1/AS1 Table 2—when used in level access routes, slopes, and stairs expected to remain dry under normal use. An alternative solution can be supported by results of oil-wet ramp slip resistance testing to DIN 51130. GTI MAX achieved an oil-wet ramp slip resistance rating of R10.
F2 (Hazardous building materials) F2.3.1	Low emission of volatile organic compounds (VOCs) has been established through FloorScore certification.

Scope of use and Limitations

Scope	Limitation
For all building classified uses	• GTI MAX Interlocking Vinyl Tiles are for interior use only. • Flooring must be laid in accordance with Belgotex NZ Installation Instructions. • GTI MAX is not suitable for loose-lay installation within 1.5 metres of a sanitary fixture or appliance.
For use in access routes	• GTI MAX is suitable for use in access routes.
In connection with underfloor heating including in-slab piped water heating.	• GTI MAX is suitable for use with underfloor heating not exceeding 28°C.

Conditions of use

GTI MAX Interlocking Vinyl Tiles must be installed according to Belgotex NZ Installation Instructions and Industry [Best Practice Guidelines](#) published by FloorNZ, and maintained according to Belgotex NZ Care & Maintenance Guidelines available at www.belgotex.co.nz.

Additional Information

For all specification, installation, maintenance and warranty information, and all information supporting Belgotex NZ claims, refer to www.belgotex.co.nz.

Responsible Person

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm GTI MAX Interlocking Vinyl Tiles, as referred to in this statement, is not subject to a warning or ban issued under [Section 26 of the Building Act](#).

Signed for and on behalf of Belgotex New Zealand Limited

Jeremy Parish

Managing Director

28/11/2025