




KÄHRS LIFE **ACCESSORIES**





Used where a wooden floor reduces down to the level that your new wooden flooring is installed against.

Height 12mm | Width 42mm Length 2400mm




T-MOULD

T-mouldings are used in transition between floors of the same height.

Comes with track system for easy installation.

Height 12mm | Width 58mm Length 2400mm



BELGOTEX AQUA ELITE UNDERLAY

Engineered to significantly reduce both reflected footfall and transmitted noise from upper-story traffic, Aqua Elite ensures a serene and peaceful environment below. Whether you're walking softly or bustling around, this underlay keeps your space quiet and comfortable.

Designed to work seamlessly with underfloor heating and cooling systems, Aqua Elite offers year-round comfort. When installed over a flat, smooth sub-floor, it provides a firm, luxurious feel underfoot, enhancing the longevity and performance of your new floor for years to come.

Roll Length 25m | Roll Width 1m | Thickness 2.5mm Water Vapour Diffusion Resistance (SD) >75m Compression Strength (CS) 109kPa



STAIR NOSING

Our nosing adds the finishing touch to your rooms with steps or stairs, blending with the design you select for your floor.

Length 1810mm | Width 150mm

AVAILABLE IN THESE COLOURS



COCONUT CREAM



WHOLE GRAIN

LIGHT SUEDE

EARL GREY



FADED BLACK



BELGOTEX AQUA PERFORMANCE UNDERLAY

Aqua Performance sets the standard for quality in floating floor underlays. At Belgotex, we prioritize indoor air quality, which is why we use only the finest materials to ensure a safe and healthy environment for you and your family. Built to last, Aqua Performance is guaranteed to protect your flooring investment for years to come, featuring an integrated vapour barrier and convenient peel-and-stick tape for easy installation.

Roll Length 50m | Roll Width 1m | Thickness 2.0mm Water Vapour Diffusion Resistance (SD) > 75m Compression Strength (CS) 42kPa





PURE WALNUT



COCOA BEAN



Contact Us





