

REACTION TO FIRE CLASSIFICATION REPORT N° 2014/001-2

(English report of classification report N°2014/001-1)

According to EN 13501-1 (2007) + A1 (2013) - EN 13501-1 (2018)

Notification by the French Government to the European Commission under n° NB 2401 Regulation (UE) n° 305/2011

Sponsor:

BALSAN

Corbilly Arthon

36330 LE POINCONNET

FRANCE

Product name:

Family group carpet tiles polyamide on bitumen backing

Description:

Textile floor coverings (EN 1307 family)

(see detailed description in paragraph 2)

Date of issue:

11/04/2025 (update)

The indicated classification does not prejudge the conformity of marketed materials with the samples submitted to the tests and under no circumstances, this document should not be considered as type approval or certification of the product in the sense of the L 115-27 article of the consumption's code of the law.

The reproduction of this classification report is only authorised in its integral form. It comprises 6 pages

1. Introduction

This classification report defines the classification assigned to the above-mentioned products in accordance with the procedures given in the NF EN 13501-1 standard: September 2007 & A1 (2013) – EN 13501 (2018).

2. Details of classified product

2.1. Product standard

NF EN 14041 (2005): «Resilient, textile and laminate floor coverings - Essential characteristics.

2.2. Product description

Tufted carpet tile 100% polyamide on bitumen backing (EN 1307 family).

Tested loose laid over a fibre-cement board classified $A1_{fl}$ or $A2_{fl}$ with a density (1800 ± 200) kg/m³ and thickness (8 ± 2) mm.

Use surface: 100 % polyamide

Nominal mass per unit area : 3955 to 4920 g/m² Nominal effective pile thickness : 0.6 to 5.8 mm

3. Test reports and tests results in support of this classification

3.1. Tests reports

Name of laboratory	Name of sponsor	Test report N°	Test method
	BALSAN		
CDET	Corbilly Arthon	RL 2025/164 (1-2)	EN ISO 9239-1
C.R.E.T.	36330 LE POINCONNET	(11/04/2025)	EN ISO 11925-2
	FRANCE		

Name of laboratory	Name of sponsor	Test report N°	Test method
C.R.E.T	BALSAN Corbilly Arthon 36330 LE POINCONNET FRANCE	RL 2020/685 (06/11/2020)	EN ISO 9239-1

Name of laboratory	Name of sponsor	Test report N°	Test method
C.R.E.T	BALSAN Corbilly Arthon 36330 LE POINCONNET FRANCE	RL 2022/545 (1-2) (29/08/2022)	EN ISO 9239-1 EN ISO 11925-2

3.2. Tests results

Classes of reaction to fire for textile floor coverings, classified without further testing.

Test method	The flooring « WINTER » meets the requirements of table 2 of the standard	
	NF EN 14041 (2015) and is classified without further testing (CWFT)	
EN ISO 11925-2	Classification E _{fl}	

		ri—	Results	
Test method	Product	Number of tests	Parameters	Compliance parameters
EN ISO 11925-2	SERENITE DALLE		Fs ≤ 150 mm	Compliant
Surface exposure- 15 secondes	(CRET report RL 2025/164-2)	6	Ignition of the filter paper	Compliant

			Results	
Test method	Product	Number of tests	Parameters	Compliance parameters
EN ISO 11925-2	UP DOWN		Fs ≤ 150 mm	Compliant
Surface exposure-	(CRET report RL 2022/545-2)	6	Ignition of the filter paper	Compliant

Classification: Ef

				Results
Test method	Product	Number of tests	Parameters	Continuous parameters: mean value
EN 190 0220 1	SERENITE DALLE	2	Critical heat flux (kW/m²)	8,7
EN ISO 9239-1	(CRET report 2019/556-1)	3	Smoke (% X min)	176,6

				Results
	Number of			Continuous
Test method	Product	tests	Parameters	parameters :
		icsis		mean value
EN 100 0000 1	EN ISO 9239-1 WINTER (CRET report 2020/685)	3	Critical heat flux (kW/m²)	8,3
EN ISO 9239-1			Smoke (% X min)	127,9

175					Results
	Test method	Product	Number of tests	Parameters	Continuous parameters: mean value
	ENLIGO 0220 1	UP DOWN	2	Critical heat flux (kW/m²)	8,1
	EN ISO 9239-1	GO 9239-1 (CRET report 2022/545-1)		Smoke (% X min)	48,2

4. Classification and field of application

4.1. Reference of classification

This classification has been carried out in accordance with EN 13501-1 :2007 & A1 (2013) - EN 13501-1 (2018).

4.2. Classification

Fire behaviour		Smoke production
\mathbf{B}_{fi}	-	s1

Classification: B_{fl}-s1

4.3. Field of application

This classification is valid for the following end use applications:

Loose laid over fibre-cement A1_{fl} or A2_{fl} with a density $\geq 1350 \text{ kg/m}^3$.

This classification is valid for the following product parameters:

A nominal mass per unit area of: 3955 to 4920 g/m²

• A nominal effective pile thickness of: 0,6 to 5,8 mm

The classification of the product family is valid for the following trademarks:

ALIZE

AVENUE

BATIK

BOLERO

BOLERO Planks

BROOKLYN

DELTA

DESERT

ENCRE DALLE

FLOW

FOREST

FREEDOM

GRAND HOTEL DALLE

GROOVE

IMPACT

IMPRESSION

INFINI COLORS

INFINI COLORS Planks

INFINI COLORS PI

JUNGLE

KARMA

LAKE

L480

LANDSCAPE

LOUVRE DALLE

MAQUIS

METROPOLITAN DISTRICT

METROPOLITAN GRAFIK

MEZZO

MISTRAL

MODULAR DESIGN 620 LOOP

MODULAR DESIGN 650 VELOURS

MODULAR DESIGN 1030 SAXONY

MODULAR DESIGN 1240 LCL

NIRVANA

NUAGE - CIRRUS

NUAGE - STRATUS

ODEON

ORIGAMI

PILOTE²

PILOTE² Planks

PILOTE 3D

PROGRESSION

RAIN

RESONANCE

RIALTO DALLE

RIVER

ROCK

SAVANE

SEASONS LINES

SEASON LINES Planks

SERENITE DALLE

SERENITE DALLE LINES

SIMOUN

SIROCCO

SOHO

STEPPE

STONE AGE

STONE AGE PI

STREAM

SYDNEY DALLE

TAKE A WALK

TOP DESIGN BOLERO DALLE

TOUNDRA

TRACK

TRAMONTANE

TRUST

TRUST LINES

TRUST LINK

TRUST STRIPES

ULTRASOFT DALLE

ULTRASOFT Planks

UP DOWN

URBANIST

VOYAGER

WINTER

WINTER Planks

ZEPHYR

5. Limitations

This classification document does not represent type approval or certification of the product.

"The classification assigned to the product in this report is appropriate to a declaration of conformity by the manufacturer within the context of system 3 of AVCP and CE marking under the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of constructions products.

The manufacturer has made a declaration, which is held on file. This confirms that the products design requires no specific processes, procedures or stages (no addition of flame-retardants, limitation of organic content, or addition of fillers) that are aimed at enhancing the fire performance in order to obtain the classification achieved. As a consequence the manufacturer has concluded that system 3 attestation is appropriate.

The test laboratory has, therefore, played no part in sampling the product for the test, although it holds appropriate references, supplied by the manufacturer, to provide for traceability of the samples tested."

For the SARL C.R.E.T. The Technical Director Marc WELCOMME

End of the classification report